



# COVERPRO™<sub>15</sub>

## SYNTHETIC ROOFING UNDERLAYMENT

15 lb Felt Replacement

### PRODUCT INFORMATION

#### PRODUCT OVERVIEW

Now you have a choice - CoverPro™ 15 is the best synthetic underlayment to combine the value-added performance of synthetic underlayment with the cost of 15 lb roofing felt. CoverPro™ 15 provides the synthetic features you demand for fast, simple installation and robust performance under asphalt shingle roofing. Manufactured from 100% synthetic materials, CoverPro 15 is the engineered solution that finally offers the performance you need, at a price competitive with 15 lb felt. Faster installation, better installed performance, a 10-year limited warranty and full-color Broadcast® custom printed advertising powered by WRAPLAB™ makes CoverPro 15 the right choice for your next job.

#### FEATURES

- **BROADCAST® Custom Printing:** Huge, full-color print with alternating full-size images.
- **Simple to Apply:** CoverPro™ 15 installs quickly, easily and has 17% more coverage per course than a standard roll of 15 lb felt.
- **Reliable:** Unlike felt, CoverPro™ 15 is highly water-repellent, keeping CoverPro 15 from warping, wrinkling and cracking in cold weather.
- **Improved Handling:** Less weight per roll makes CoverPro™ 15 easier to handle during all stages of installation.
- **Warranty:** A 10-year limited warranty applies to CoverPro™ 15. See [coverpro-underlayment.com](http://coverpro-underlayment.com) for more details.

#### TYPICAL PHYSICAL PROPERTIES

PROPERTY	STANDARD	UoM	TYPICAL RESULT <sup>1</sup>
Water Vapor Permeance	ASTM E 96, Method A	perms	0.1
Water Transmission	ASTM D 4869	Pass/Fail	Pass
Tear Strength (MD/CD)	ASTM D 4533	lbs	26 / 24
Tensile Strength (MD/CD)	ASTM D 751	lbs	83 / 71
Burst Strength	ASTM D 751	psi	130
Elongation	ASTM D 751	%	18
Basis Weight	ASTM D 5261	g/m <sup>2</sup>   lbs/square	110   2.25
Nominal Thickness	ASTM D 1117	mils (0.0001")	7
Temperature Range	Internal	--	-70 to 212°F (-55 to 100°C)

<sup>1</sup> Results reflect typical properties of control/non-conditioned specimens. Values should not be interpreted as limiting specifications and will vary within typical manufacturing tolerances.

#### ROLL SIZES

40" (+/- 0.5") x 300'

#### CODE AND STANDARD COMPLIANCE

##### ASTM D 226, TYPE I

Standard Specification for Asphalt-Saturated Organic Felt Used in Roofing and Waterproofing

##### CSA A 123.3

Asphalt Saturated Organic Roofing Felt

##### FBC Approval #8700

# COVERPRO™<sub>15</sub>

System Components Corporation  
P.O. Bo 2432  
Issaquah, WA 98027